

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. – 39. (Cancelled)
40. (New) A voice data transmitting system, comprising:
 - a communication terminal configured to generate packets based on voice data;
 - a voice recognizer unit configured to determine divisions of utterances represented by the voice data, and configured to divide the voice data into clause units in accordance with the divisions; and
 - a packet combine unit configured to combine, for each of the clause units, every packet of said packets that includes portions of the voice data for the clause unit into a corresponding single packet.
41. (New) The voice data transmitting system of claim 40,
 - said packet combine unit configured to transmit, for each of the clause units, the corresponding single packet over a communication path.
42. (New) The voice data transmitting system of claim 40, further comprising:
 - a file producer unit configured to produce, for each of the clause units, a corresponding file including the corresponding single packet.
43. (New) The voice data transmitting system of claim 42,
 - said file producer unit configured to transmit, for each of the clause units, the corresponding file.
44. (New) The voice data transmitting system of claim 42,
 - said file producer unit configured to include, for each of the clause units, discrimination data in the corresponding file indicating contents of the corresponding file.

45. (New) The voice data transmitting system of claim 42, further comprising:

a transmission monitoring unit configured to determine a communication state as at least one of a first state, a second state, and a third state;

said voice data transmitting system configured to (i) transmit said packets in a case where said transmission monitoring unit determines said communication state as being said first state, (ii) transmit, for each of the clause units, the corresponding single packet in a case where said transmission monitoring unit determines said communication state as being said second state, and (iii) transmit, for each of the clause units, the corresponding file in a case where said transmission monitoring unit determines said communication state as being said third state.

46. (New) The voice data transmitting system of claim 40, further comprising:

a transmission monitoring unit configured to determine a communication state as at least one of a first state and a second state;

said voice data transmitting system configured to (i) transmit said packets in a case where said transmission monitoring unit determines said communication state as being said first state, and (ii) transmit, for each of the clause units, the corresponding single packet in a case where said transmission monitoring unit determines said communication state as being said second state.

47. (New) The voice data transmitting system of claim 40,

said communication terminal configured to generate said packets as real-time communication packets.

48. (New) The voice data transmitting system of claim 40,

said packet combine unit configured to retransmit, upon receiving a retransfer request for a clause unit of said clause units, the corresponding single packet for the clause unit.

49. (New) The voice data transmitting system of claim 40,
said voice recognizer unit configured to determine said divisions based on a sound level of a voice that produces the utterances represented by the voice data.
50. (New) The voice data transmitting system of claim 40,
said voice recognizer unit configured to determine said divisions based on a sound pitch of a voice that produces the utterances represented by the voice data.
51. (New) The voice data transmitting system of claim 40,
said voice recognizer unit configured to determine said divisions based on a movement of lips of a user that produces the utterances represented by the voice data.
52. (New) The voice data transmitting system of claim 40,
said voice recognizer unit configured to determine said divisions based on vibrations of a throat of a user that produces the utterances represented by the voice data.
53. (New) The voice data transmitting system of claim 40,
said voice recognizer unit configured to determine said divisions based on externally provided instructions.
54. (New) A method of creating voice packets, comprising:
generating packets based on voice data;
determining divisions of utterances represented by the voice data;
dividing the voice data into clause units in accordance with the divisions; and
combining, for each of the clause units, every packet of said packets that includes portions of the voice data for the clause unit into a corresponding single packet.
55. (New) The method of claim 54, further comprising:
transmitting, for each of the clause units, the corresponding single packet over a communication path.

56. (New) The method of claim 55, further comprising:

retransmitting, upon receiving a retransfer request for a clause unit of said clause units, the corresponding single packet for the clause unit.

57. (New) The method of claim 54, said generating comprising:

generating said packets as real-time communication packets.

58. (New) The method of claim 54, further comprising:

producing, for each of the clause units, a corresponding file including the corresponding single packet.

59. (New) The method of claim 58, further comprising:

transmitting, for each of the clause units, the corresponding file over a communication path.

60. (New) The method of claim 58, said producing comprising:

including, for each of the clause units, discrimination data in the corresponding file that indicates contents of the corresponding file.

61. (New) The method of claim 58, further comprising:

determining a communication state as at least one of a first state, a second state, and a third state;

transmitting said packets over a communication path in a case where the communication state is determined to be said first state;

transmitting, for each of the clause units, said corresponding single packet over the communication path in a case where the communication state is determined to be said second state; and

transmitting, for each of the clause units, said corresponding file over the communication path in a case where the communication state is determined to be said third state.

62. (New) The method of claim 54, further comprising:
determining a communication state as at least one of a first state and a second state;
transmitting said packets over a communication path in a case where the
communication state is determined to be said first state; and
transmitting, for each of the clause units, said corresponding single packet over the
communication path in a case where the communication state is determined to be said second
state.
63. (New) The method of claim 54, said determining comprising:
determining said divisions based on a sound level of a voice that produces the
utterances represented by the voice data.
64. (New) The method of claim 54, said determining comprising:
determining said divisions based on a sound pitch of a voice that produces the
utterances represented by the voice data.
65. (New) The method of claim 54, said determining comprising:
determining said divisions based on a movement of lips of a user that produces the
utterances represented by the voice data.
66. (New) The method of claim 54, said determining comprising:
determining said divisions based on vibrations of a throat of a user that produces the
utterances represented by the voice data.
67. (New) The method of claim 54, said determining comprising:
determining said divisions based on externally provided instructions.

68. (New) A voice data receiving system, comprising:

a packet division unit configured to divide each of a plurality of received packets into a corresponding plurality of real-time communication packets; and

a communication terminal configured to reproduce voice data based on the corresponding plurality of real-time communication packets for each of the plurality of received packets.

69. (New) A method of processing packets received over a communication path, the method comprising:

receiving a plurality of packets over the communication path;

dividing each of the plurality of packets into a corresponding plurality of real-time communication packets; and

reproducing voice data based on the corresponding plurality of real-time communication packets for each of the plurality of packets.